



BRINCO ANPQ OIL

Oil for industrial chemical processes made from carefully selected naphthenic bases with a medium viscosity index. It is specially formulated for applications such as process oil and plasticizer.

USES

- Process oil in the Chemical Industry.
- Lubricating oil in the textile industry.
- In mechanical components that work at low temperatures that require a pure mineral.

PROPERTIES

- Very good characteristics at low temperatures.
- Low pour point
- Low tendency to form waxes.
- Softener in rubber processes of the NR (natural rubber), SBR (Styrene Butadiene) and BR (Polybutadiene) types.
- Low odor.

TYPICAL PROPERTIES

PHYSICOCHEMICAL TESTS	UNIT	METHOD	AVERAGE VALUES		
ISO VG grade		-	15	22	40
Color		ASTM D-1500	0.5	0.5	2
Density @ 15°C	Kg/L	ASTM D-4052	0.886	0.86	0.904
Kinematic Viscosity @ 40°C	cSt	ASTM D-445	15	22	40
Kinematic Viscosity @ 100°C	cSt	ASTM D-445	3.1	4.0	5.6
Viscosity index		ASTM D-2270	47	57	65
Flashpoint	°C	ASTM D-92	150 min.	160 min.	180min.
Pour point	°C	ASTM D-97	-40	-40	-40

In the batches manufactured there may be slight variations in the average values, which do not affect the quality or the performance of the product.

- Light colors.

HEALTH AND SAFETY

This product does not present a risk to health or safety as long as they maintain good personal and industrial hygiene practices. In case of contact with the skin, wash immediately with soap and water.

Wear gloves to handle used oils. Do not dispose of the residue down the sewer. Take care of our environment.

AVAILABLE SIZES

BRINCO ANPQ OIL
55 gal cylinder
5 gal bucket