



BRINCO APPQ OIL

Lubricating oil for industrial chemical processes made with carefully selected paraffinic bases with a high viscosity index. It is specially formulated for application as a process oil.

USES

- Process oil in the Chemical Industry.
- Lubricating oil in the textile industry.
- In mechanical components that work at low temperatures that require a pure mineral.

PROPERTIES

- Very good chemical stability so the oil is preserved when in contact with high temperatures.
- High viscosity index.
- Great resistance to oxidation.

HEALTH AND SAFETY

This product does not present a risk to health or safety as long as they maintain good personal and industrial hygiene practices. In case of contact with the skin, wash immediately with soap and water. Wear gloves to handle used oils. Do not dispose of the residue down the sewer. Take care of our environment.

AVAILABLE SIZES

BRINCO APPQ OIL
55 gal cylinder
5 gal bucket

TYPICAL PROPERTIES

PHYSICOCHEMICAL TESTS	UNIT	METHOD	AVERAGE VALUES		
ISO VG grade		-	32	68	100
Color		ASTM D-1500	2	2	3
Density @ 15°C	Kg/L	ASTM D-4052	0.86	0.877	0.902
Kinematic Viscosity @ 40°C	cSt	ASTM D-445	32	68	100
Kinematic Viscosity @ 100°C	cSt	ASTM D-445	5.7	8.8	11.6
Viscosity index		ASTM D-2270	119	102	104
Flashpoint	°C	ASTM D-92	150 min.	200 min.	200 min.

In the batches manufactured there may be slight variations in the average values, which do not affect the quality or the performance of the product.