

CRISOLI 22

Highly refined mineral oils of great use for industrial lubrication, it offers great performance where oxidation and rust are not a problem. It is a non-additive lubricant.

PROPERTIES

- High viscosity index.
- Good thermal stability, thus guaranteeing good performance during work.
- Stability against corrosion and rust formation.
- Prevents the formation of lacquers and sludge.

HEALTH AND SAFETY

This product does not present a health or safety risk as long as good personal and industrial hygiene practices are maintained. In case of skin contact, wash immediately with soap and water.

AVAILABLE SIZES

CRISOLI 22
5 gallon bottle
55 gal cylinder

TYPICAL PROPERTIES

PHYSICOCHEMICAL TESTS	UNIT	METHOD	AVERAGE VALUES
ISO grade		-	22
Color		Visual	Colorless-Yellow
Density @ 15.6°C	Kg/L	ASTM D-4052	0.8600
Kinematic Viscosity @ 40°C	cSt	ASTM D-445	22
Kinematic Viscosity @ 100°C	cSt	ASTM D-445	4.3
Viscosity index		ASTM D-2270	100
Flashpoint	°C	ASTM D-92	200 min.
Pour point	°C	ASTM D-97	-5 máx.

In the batches manufactured there may be slight variations in the average values, which do not affect the quality or the performance of the product.