



MOLYGRAF GREASE

Made with lithium soap thickener, high viscosity index base oils, extreme pressure additives, antioxidants, anticorrosives and a high content of premium quality colloidal graphite, reducing the friction coefficient of ball joints, bearings, wheel bearings to the maximum. , etc.

USES

It is recommended to lubricate the bearings, prolonging the useful life of the tracks and of this part as a whole.

In the lubrication of the chassis elements in heavy vehicles and especially for those equipment that requires frequent lubrication due to the presence of dust such as tractors, mining equipment and / or cement and construction factories.

Also recommended on industrial rails or guides. These mechanisms must be lubricated with a certain frequency.

PROPERTIES

- Provides protection against rust, corrosion and water washout.
- Excellent mechanical stability.
- It is recommended for applications in temperatures below 121° C.

- The addition of graphite confers optimal ability to bear loads, reduce friction and wear.

HEALTH AND SAFETY

This product does not present a risk to health or safety as long as good personal and industrial hygiene practices are maintained. In case of skin contact, wash immediately with soap and water.

AVAILABLE SIZES

MOLYGRAF GREASE
397 g tube
35 Lb bucket

TYPICAL PROPERTIES

PHYSICOCHEMICAL TESTS	UNIT	METHOD	AVERAGE VALUES
NLGI grade	-	-	2
Color	-	Visual	Gray
Soap Type	-	-	Lithium
Penetration @ 77 ° F (25 ° C)	0.1mm	ASTM D-217	270
Dropping point	°C	ASTM D-2265	183
Oil viscosity @ 40 ° C	cSt	ASTM D-445	220
Oil viscosity @ 100 ° C	cSt	ASTM D-445	15.8
Rust protection		-	Suitable
Low temperature condition	°C	-	-20
High temperature condition	°C	-	121

In the batches manufactured there may be slight variations in the average values, which do not affect the quality or the performance of the product



FC VIS – AT – FC – 01
Version 1 – June 2021