

VISTOBLOCK is an NLGI 6 grade block lubricating grease, made from hard type sodium soap with highly refined oils and extreme pressure additives. It is of a consistent and uniform texture, slightly fibrous and brown in color. Vistoblock grease has a good lubricating film that reduces friction during operation.

USES

VISTONY

VISTOBLOCK is recommended for plain bearings and mill shafts (balls or bar) made of bronze material or tin, copper, lead alloys for industrial plants, mining, cement and other machine applications where a block-shaped grease is required. such as (ovens, crushers, dehydrators) and that the working temperature is moderate.

The application of the block inside the machine is through the rest of the block/ the moving parts of the machine. It is recommended to place an appropriate weight of grease for better lubrication.

PROPERTIES

- Reduces friction between surfaces in contact.

- Protects metal surfaces against corrosion and rust formation.

- It has great adhesiveness, which allows it to remain in the lubricated element.

- The base oil used gives consistency to the lubricating film, thus allowing it to withstand very heavy loads.

- It is recommended to place a certain appropriate weight on the grease for better lubrication.

HEALTH AND SAFETY

This product does not present a risk to health or safety as long as good personal and industrial hygiene practices are maintained.

In case of contact with the skin, wash immediately with soap and water.

Do not dispose of your waste into the sewer. Protect our environment.



TYPICAL PROPERTIES

PHYSICOCHEMICAL TESTS	UNIT	METHOD	AVERAGE VALUES
NLGI grade	-	-	6
Color	-	VISUAL	Light brown
Soap Type	-	-	Sodium
Texture	-	-	Fibrous
Penetration, @ 60 $^{\circ}$ F @ 25 $^{\circ}$	0.1mm	ASTM D-217	<85-115>
Dropping point	°C	ASTM D-2265	140
Oil viscosity @ 40 ° C	cSt	ASTM D-445	200
Soap content	% weight	-	35

The specifications are average values. In the manufactured batches there may be slight variations that do not affect the quality of the product, or the performance

AVAILABLE SIZES

GREASE VISTOBLOCK

• 20x25x30cm bars (20Kg)

FC VIS – AT – FC – 016 Version 1 – June 2021