

TEXOIL

Lubricating oil, formulated for the textile industry, protecting against friction, wear and corrosion. Texoil Vistony, has special components that allow it to be easily removed from fabrics during the washing process, such as knife oil in the paper industries and in general for all those parts that work in high speed and low load conditions.

USES

In the textile industry rings, sewing machine parts, double circular knitting machines, in the paper industry blades.

PROPERTIES

- Completely colorless, does not stain fabrics and textile fibers.
- Protection against wear, rust and corrosion.
- Natural capacity for cleaning.
- It has a great stability to oxidation.

HEALTH AND SAFETY

This product does not present a health or safety risk as long as good personal and industrial hygiene practices are maintained. In case of contact with the skin, wash immediately with soap and water.

AVAILABLE SIZES

TEXOIL
• 5 gallon bottle
55 gal cylinder
3.785 L gallon
0.946 L bottle

TYPICAL PROPERTIES

PHYSICOCHEMICAL TESTS	UNIT	METHOD	AVERAGE VALUES		
ISO grade		-	15	22	32
Color		Visual	Colorless		
Relative Density @ 15 ° C	Kg/L	ASTM-4052	0.884	0.874	0.870
Kinematic Viscosity @ 40°C	cSt	ASTM D-445	15	22	32
Kinematic Viscosity @ 100°C	cSt	ASTM D-445	3.36	4.34	5.54
Viscosity index		ASTM D-2270	91	104	110
Flashpoint	°C	ASTM D-92	200 min.	208 min.	230 min.
Pour point	°C	ASTM D-97	-20.	-10	-8

In the batches manufactured there may be slight variations in the average values, which do not affect the quality or the performance of the product.